

NO Readme Files	Series NO SQ1-511W			
	Name:Spark Quencher			
	Descripting			
Single Phase / Operating Voltage Max.- 550VAC				

PRODUCT DESCRPTION

Type	Lead Wire Type			PCB Type
Model	SQ1-511W	SQ3-351W	SQ3-511W	SQ1-115P
Phase	Single Phase	Three Phase		Single Phase
Operating Voltage max.	550VAC	300VAC	550VAC	250VAC
Value of Condenser	0.1 μ F	0.47 μ F	0.1 μ F	0.1 μ F
Value of Resister	100 Ω	100 Ω	100 Ω	510 Ω
Wattage of Resister	2W			
Frequency of Voltage	50/60Hz			
Max. Durated Voltage	750Vp-p/1ms	900Vp-p/1ms	1500Vp-p/1ms	500Vp-p/1ms
Isolation Strength	100M Ω /500VDC			
Dielectric Strength	2.5KVAC/1min.			
Operating Temp/Hum.	-25 $^{\circ}$ C ~ +70 $^{\circ}$ C ; -35 $^{\circ}$ C ~ +95 $^{\circ}$ C			
Material of Housing	Intensive PBT			
Length of Wire	10cm			Without
Weight	Appr.13g	Appr.35g	Appr.35g	Appr.4.5g