

DATASHEET

Power-Relay-Socket

with screw eye and extension receptacle,
2 x 9,5 mm + 3 x 6,3 mm + 4 x 2,8 mm

order number: N2-1021-0011
version of 03.11.2017

1. Technical data

| | |
|------------------------|---|
| Nominal voltage: | 6 – 48 V |
| Operating temperature: | - 40 to 85 °C (- 40 to 185 °F) |
| Material: | PA6.6 GF30 |
| Color: | black |
| Weight: | approx. 23 g |
| Contact arrangement: | 2 x Flat push-on receptacle 9,5 x 0,8, for example X7-2273-0101 (4 ... 6 mm ²) X7-2273-5102 (6 ... 10 mm ²) 3 x Flat push-on receptacle 6,3 x 0,8, for example X7-2011-0100 (0,5 ... 1 mm ²) X7-2012-0110 (1,5 ... 2,5 mm ²) 4 x Flat push-on receptacle 2,8 x 0,8, for example X7-2211-0021 (0,5 ... 1 mm ²) |
| Mating connector: | Tabs according to DIN EN ISO 8092-1 |
| Assembly: | M5 bolt mounting, single or as block, Frontal extension for another socket, for example K9-1120-0010 K9-1120-0011 |



2. Dimensions

See Appendix A : Data sheet drawing