

Description

| | |
|-------------------------|--|
| Identnumber | 00169344 |
| Key | 2000-A-2-65,0-EE-VA-SD48-C-H * NK51 |
| BSTALT | |
| Description | 2/2-way-piston-operated angle-seat valve |
| Type (TYP) | 2000 - 2000 |
| Control function (SF) | A - closed by spring force |
| Paths/positions (WS) | 2 - 2 ways / 2 position |
| Orifice size (DN) | 65,0 - 65mm (2 1/2") |
| Seal material (DWST) | EE - PTFE |
| Body material (WKST) | VA - stainless steel |
| Port connection (LTA) | SD48 - Weld end 70,0 x 2,0 accor ding to DIN 11850 series 2, DIN 11866 series A, DIN EN 10357 series A |
| Actuator version (ANTA) | C - PA-actuator, VA-threaded bus hing at connection of pilot air |
| Actuator size (ANTG) | H - Dm 125mm |
| Variable Code 1 (VAR1) | NK51 - packed seal enclosed |
| Substitute-ID | |
| ConformitySign | CEEX |
| Delivery Time | 14 Calender Days |

Technical Data

| | |
|---|-------|
| PRESS. MAX. (BAR) (DRMAXBAR) | 5.2 |
| PRESS MAX. (PSI) (DRMAXPSI) | 75 |
| PRESS. MIN. (BAR) (DRMINBAR) | 0 |
| PRESS. MIN (PSI) (DRMINPSI) | 0 |
| REQUIRED PILOT PRESS.F.MAX.FLUID PRESS.(BAR) (STDRERFBAR) | |
| REQUIRED PILOT PRESS.F.MAX.FLUID PRESS.(PSI) (STDRERFPSI) | |
| PILOT PRESS. MAX (BAR) (STDRMAXBAR) | 7 |
| PILOT PRESS MAX. (PSI) (STDRMAXPSI) | 100 |
| PILOT PRESS. MIN. (BAR) (STDRMINBAR) | 3.2 |
| PILOT PRESS. MIN. (PSI) (STDRMINPSI) | 46 |
| KV-VALUE (M ³ /H) (KV) | 90.0 |
| QNN-VALUE (L/MIN) (QNN) | |
| WEIGHT (KG) (MASSE) | 11.00 |
| FLUID TEMP. MAX. (DEGREE C) (MEDTEMPMAX) | 180 |
| FLUID TEMP. MIN. (DEGREE C) (MEDTEMPMIN) | -10 |
| AMB. TEMP. MAX. (DEGREE C) (UMGTEMPMAX) | 60 |
| AMB. TEMP. MIN. (DEGREE C) (UMGTEMPMIN) | -10 |